



SUPPLIERS OF NEW & USED BOTTLING MACHINERY FOR OVER 40 YEARS

14, Crane Mead Business Park, Ware, Herts, SG12 9PZ, England Tel: 01920 484050 Fax: 01920 484050 E-mail: info@acosales.co.uk Web site: www.acosales.co.uk

Make: ACO

Model: Semi-automatic floor standing counter pressure filling machines & carbonators

Year : NEW

STANDARD MACHINE SPECIFICATIONS (All details are for guidance only, and subject to confirmation)

Manually operated machine manufactured from AISI 304 stainless steel. Suitable for filling glass or plastic bottles with mineral water, carbonated soft drinks, beer and other types of carbonated drinks such as sparkling wine etc. Optimal shape of the filling nozzle prevents flattening or foaming of the liquid.

2,4,6 and 8 heads are the standard sizes. Due to its simple operation the machine is ideal for small bottlers. The bottle filling machine can be connected directly to our carbonating equipment. The frame is adjustable according to the required standard bottle sizes from 0,2 litres up to 2 litres. For non-standard sizes the bottle filling machine is individually designed on the basis of the respective sample. The filling level can be adjusted separately on each nozzle. Each machine is supplied with a dummy bottle in stainless steel and a CIP spray ball to allow cleaning inside the pressure tank.

Method

Insert bottle on to spring loaded pedestal, pull lever ¼ down for 1 second which inserts co2, pull lever completely down which starts the fill cycle to an automatic fill height stop point which you have pre-set, return the handle to the start point which automatically lets the gas escape to stop foaming.

Filling Machines

CP2 head: 175 Bph 600x830x1600 mm x 60kg CP4 head: 350 Bph 800x830x1600 mm x 70kg

CP6 head: 500 Bph 1100x830x1600 mm high x 80kg CP8 head: 650 Bph 1300x830x1600 mm high x 90kg

Export shipping crates available Service pressure: max. 4 bar

Carbonators

C1000 - 1000 Lph for pre-mixed products C3000 - 3000 Lph for pre-mixed products

Infeed pump connected mechanically and electrically

Option to change electricity supply to single phase

Pressure: 3-4 bar, Connection: C1/2", Temp: up to 10 °C, Electrical: 400v-50Hz-3ph 2 kW, Content of CO2: 4-10q

Dimensions (LxWxH): 800x630x1700 mm, Weight: approx. 150 kg.

Export shipping crates available





SUPPLIERS OF NEW & USED BOTTLING MACHINERY FOR OVER 40 YEARS

14, Crane Mead Business Park, Ware, Herts, SG12 9PZ, England Tel: 01920 484050 Fax: 01920 484050 E-mail: info@acosales.co.uk Web site: www.acosales.co.uk





