

### SUPPLIERS OF NEW & USED BOTTLING MACHINERY FOR OVER 40 YEARS

14, Crane Mead Business Park, Ware, Herts, SG12 9PZ, England Tel: 01920 484050 Fax: 01920 484050 E-mail: info@acosales.co.uk Web site: www.acosales.co.uk

# Model :Semi-automatic floor standing counter pressure filling machines & carbonatorsYear :NEW

STANDARD MACHINE SPECIFICATIONS (All details are for guidance only, and subject to confirmation)

Manually operated machine manufactured from AISI 304 stainless steel. Suitable for filling glass or plastic bottles with mineral water, carbonated soft drinks, beer and other types of carbonated drinks such as sparkling wine etc. Optimal shape of the filling nozzle prevents flattening or foaming of the liquid.

2,4,6 and 8 heads are the standard sizes. Due to its simple operation the machine is ideal for small bottlers. The bottle filling machine can be connected directly to our carbonating equipment. The frame is adjustable according to the required standard bottle sizes from 0,2 litres up to 2 litres. For non-standard sizes the bottle filling machine is individually designed on the basis of the respective sample. The filling level can be adjusted separately on each nozzle. Each machine is supplied with a dummy bottle in stainless steel and a CIP spray ball to allow cleaning inside the pressure tank.

#### Method

Insert bottle on to spring loaded pedestal, pull lever 1/4 down for 1 second which inserts co2, pull lever completely down which starts the fill cycle to an automatic fill height stop point which you have pre-set, return the handle to the start point which automatically lets the gas escape to stop foaming.

#### **Filling Machines**

CP2 head: 175 Bph CP4 head: 350 Bph CP6 head: 500 Bph CP8 head: 650 Bph Export shipping crates available Service pressure: max. 4 bar Product temperature at machine inlet: 0-4 °C 600x830x1600 mm x 60kg 800x830x1600 mm x 70kg 1100x830x1600 mm high x 80kg 1300x830x1600 mm high x 90kg

#### **Carbonators**

C1000 - 1000 Lph for pre-mixed products

C3000 - 3000 Lph for pre-mixed products

Infeed pump connected mechanically and electrically

Option to change electricity supply to single phase

Pressure: 3-4 bar, Connection: C1/2", Product temperature at machine inlet: 0-4 °C, Electrical: 400v-50Hz-3ph 2 kw, Content of CO2: 4-10g Dimensions (LxWxH): 800x630x1700 mm, Weight: approx. 150 kg. Export shipping crates available



## SUPPLIERS OF NEW & USED BOTTLING MACHINERY FOR OVER 40 YEARS

14, Crane Mead Business Park, Ware, Herts, SG12 9PZ, England Tel: 01920 484050 Fax: 01920 484050 E-mail: info@acosales.co.uk Web site: www.acosales.co.uk







All prices are in GB Pounds Sterling and are supplied ex-VAT and ex-Works unless otherwise stated. The goods hereby supplied shall remain the property of the seller until such time as payment for the product has been made in full. Any discrepancies to be made in writing within 7 days of receipt. All goods are supplied against our standard terms and conditions which are available on request. E & O.E. Company Reg. GB996055 VAT Reg. No. 801981926